

TRUTEK LV350 - SEMI-AUTOMATIC PAT

Usage:

- individual fasteners in concrete and steel with nails 12mm to 62mm long
- fixing steel drywall profiles
- fixing in electric holders and installation accessories
- individual fastening of flashings during facade assembly
- single fastening of steel and trapezoidal sheets for steel structures


PTB

Advantages:

- speed of work - setting directly in the ground without the need for drilling both in the ground and in the material being fastened
- automatic reloading of powder charge - a tape with cartridges of 10 pieces allows for 10 fastenings without shifting powder charge
- simple operation and maintenance
- highest safety of work with the fastening tool, protection against unwanted firing of powder charge
- small size and weight make work much easier

Substrate material:

Concrete and reinforced concrete class max. C30 / 37, hot rolled structural steel, solid ceramic brick, silicate block and hollow silicate block

Technical data of the LV350 nailer


Tool weight	2,35kg
Tool length	340mm
Guide diameter	8mm
Cartridge caliber	6.8 / 11 in strips of 10 pieces

Selection of ammunition depending on the type of ground

Product Code	Power	Colour	Steel <8mm	Steel >6mm	Steel >4mm	Concrete C40/45	Concrete C20/25	Concrete >C16/20	Silicate Brick	Full Brick
TCRM	Silny	Red								
TCYM	Average	Yellow								
TCGM	Weak	Green								



Use in the following tools: TRUTEK LV300MA, LV500, LV350, LV400 and HILTI DX A40, DX A41, DX 351, DX 450, DX 460, DX5



Single nails - TD for embedding in steel and concrete

Product Code	Diameter dxL [mm]	Min. Embedment depth in the ground [mm]				Max. attached element thickness [mm]			
		C16/20	C20/25	C25/30	Stal	C16/20	C20/25	C25/30	Stal
TD16	3,7x16	-	-	-	4	-	-	-	6
TD19	3,7x19	-	-	-	4	-	-	-	9
TD22	3,7x22	-	-	-	4	-	-	-	12
TD27	3,7x27	22	22	22	4	5	5	5	17
TD32	3,7x32	22	22	22	4	10	10	10	22
TD37	3,7x37	22	22	22	4	15	15	15	27
TD42	3,7x42	22	22	22	4	20	20	20	32
TD47	3,7x47	22	22	22	4	25	25	25	37
TD52	3,7x52	22	22	22	4	30	30	30	42
TD57	3,7x57	22	22	22	4	35	35	35	47
TD62	3,7x62	22	22	22	4	40	40	40	52
TD72	3,7x72	22	22	22	4	50	50	50	62
TD82	3,7x82	22	22	22	4	60	60	60	72
TD90	3,7x90	22	22	22	4	68	68	68	80
TD97	3,7x97	22	22	22	4	75	75	75	87

Use in the following tools: TRUTEK LV300MA, LV500, LV350, LV600M and HILTI DX A40, DX A41, DX 351, DX 450, DX 460, DX5



TMWP nails with a metal washer Ø23mm

Product Code	Diameter dxL [mm]	Min. Embedment depth in the ground [mm]				Max. attached element thickness [mm]			
		C16/20	C20/25	C25/30	Steel	C16/20	C20/25	C25/30	Steel
TMWP27	3,7x27	22	22	22	4	5	5	5	17
TMWP32	3,7x32	22	22	22	4	10	10	10	22
TMWP47	3,7x47	22	22	22	4	25	25	25	37

Use in the following tools: TRUTEK LV300MA, LV500, LV350, LV600M and HILTI DX A40, DX A41, DX 351, DX 450, DX 460, DX5

Strength parameters of single TD nails

Pin designation	TD
Recommended load capacity for pulling out the nail from the Nzal steel substrate [kN]	2,0
Recommended load-bearing capacity for pulling the nail out of the Nzal concrete substrate [kN]	1,0
Design load on nail shear in steel substrate and in Vzal concrete [kN]	2,0
Minimum center distance in steel in [mm]	12
Minimum inter-axle spacing in concrete C20 / 25w [mm]	75
Minimum distance from the edge in steel in [mm]	25
Minimum distance from the edge in concrete C20 / 25w [mm]	75

